



Lackfabrik Irmgard Sallinger GmbH

Technical data sheet

03/2006

IRSA REPARATURPASTE

To repair damages on wood and cork.

Basic:

Solvent-free dispersion with fillers.

Use and Characteristic:

IRSA REPARATURPASTE is available as ready-to-use, very viscous paste for over 28 types of wood and in its specific colour of cork. Available Colours: pine, mahogany, dark, dark and light oak, white, spruce, cork, beech, nut tree dark, meranti. Special colour-tones available on request.

IRSA REPARATURPASTE is universally applicable to repair varnish-painted, impregnated or untreated wood- and cork surfaces in interior areas. Also on wood imitation (laminate).

IRSA REPARATURPASTE is high adhesive, tough- flexibly and with good sanding properties. A subsequent treatment with IRSA Water-Based Varnishes, IRSA Impregnation or IRSA Wax are possible at any time after the final hardening.

Application:

Fill out the area to repair with IRSA REPARATURPASTE thoroughly with the requested colour tone. A second application might be necessary on deeper damages in the surface after several hours. Following uneven or rough parts of the paste should be carefully sanded. Take off fresh rests of the paste around the treated area only with a moist rag.

Drying Times:

Drying time with thin coats after approx. 15-30 minutes. Purely physical drying. Depending on coat strength the drying times extend differently.

Drying times refer to normal temperature-conditions of +20°C and relative air-humidity of 55%. Higher conditions of air-humidity, lower temperature and stronger coats slow down the drying process. Care for good air-circulation.

Subsequent Treatment:

In order to achieve a silky optic, we recommend a subsequent treatment 1-2 x with IRSA Water-Based Varnishes, IRSA Impregnation or IRSA Waxes.

Tools:

Especially for IRSA REPARATURPASTE, we offer the IRSA Spatula, stainless.

Only use appropriate tools for best results. Pre-clean immediately after use with papers, following clean thoroughly with water.

Sanding agents in all types are also available at IRSA.

Temperature for Processing:

Room/subsurface and IRSA REPARATURPASTE not under +15°C

Also with the processing of low-pollution joint putty, regard the usual precautions.

Cautions:

Keep out of the reach of children. Do not empty this product into drains, any stretches of water or soiled ground. Care for good air-circulation during and after processing. Do not inhale sprays. Avoid eye-and skin contact or rinse off thoroughly with water. Material and container must be disposed of in a safe way at waste collection points.

Water pollution class: WGK I

Storage:

Do not store and transport under +6°C. Shelf life of unopened original container for at least 1 year. Keep opened container tightly closed and work up soon.

Protect from cold.

The advice given by us in word, writing and endeavour for the technical application is supplied to our best knowledge, but may, however, only be regarded as an indication without any obligation and does not exempt you from examining the supplied products yourself, if they are suitable for the procedure and purposes intended. Application, use and processing of the products are not within our range of control and supervision, but are at your responsibility exclusively. It goes without saying that we guarantee products of high and good quality, according to the samples. With publishing of new information the earlier technical data sheets loose validity.