



Lackfabrik Irmgard Sallinger GmbH

Technical data sheet

07/08

IRSA Joint Sealing Compound for parquet flooring Silicon free, colourless and coloured

Sealing compound for parquet flooring joints and connection joints.

Basis: polymerised ester, silicon free.

Areas of application: sealing of joints in parquet flooring and connection joints like e.g. sealed, oiled and untreated parquet flooring and untreated wood in interior fittings and wooden window manufacture.

Colours available: maple/ash/pine, light beech, red brown beech, light oak, natural oak, dark oak, cherry, mahogany, bog oak, grey, white.

Properties: solvent free – odourless – fast drying – good for sanding when fully cured – energy elastic – excellent self adhesiveness – UV resistant and rot proof – stretchable up to 15% - and can be further treated with all standard sealants, oils and waxes – temperature and water resistance of –20°C up to +110°C when fully cured.

Method of Application:

The base must be clean, dry, dust and grease free. If necessary degrease e.g. with IRSA Basic Cleaner G88. Cut the tip off the cartridge above the thread, screw-on the nozzle, cut it across diagonally and squeeze out using a hand gun or compressed air gun. If necessary, smooth out the compound immediately with a damp sponge. For gluing apply it in a wavy line. Avoid three-sided adhesions at all costs.

Drying:

Depending on the climate and volume it can be sealed over, oiled over and/or washed over after approx 4 to 6 hours. After 18 to 24 hours it can be sanded. After approx 2 to 3 days it can be subjected to full load and wear and tear (based on the grounds of ideal conditions of +20°C und 55% humidity). High humidity and damp under flooring delay the drying process considerably.

Temperature: Room/under flooring/ IRSA Joint Sealing Compound for parquet flooring must be between +6°C and +40°C during application.

Storability:

Store and transport in cool (frost free) conditions. Storable for 1 year in an unopened, original cartridge.

Please pay attention to the instructions on the technical data sheet IRSA Joint Sealing Compound for parquet flooring.

Protect from frost!