

Safety data sheet

according to 1907/2006/EC, Article 31

Page 1/10

Printing date 20.02.2023 Version number 1.3 Revision: 20.02.2023 SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: IRSA DD- Wetterfest achatgrau ca. RAL 7038 · 1.2 Relevant identified uses of the substance or mixture and uses advised against · Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) • Product category PC9a Coatings and paints, thinners, paint removers · Process category PROC10 Roller application or brushing PROC11 Non industrial spraying • Technical function Plating agent · Application of the substance / the mixture Lacquer \cdot 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: IRSA Lackfabrik Irmgard Sallinger GmbH An der Günz 15 D-86489 DEISENHAUSEN DEUTSCHLAND Telefon:+49-82 82-89 44-0 · Further information obtainable from: Product Safety Department/ E-mail: labor@irsa.de · 1.4 Emergency telephone number: Giftnotruf Freiburg: +49-7 61-19 240 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 flame Flam. Liq. 2 H225 Highly flammable liquid and vapour. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. · Hazard pictograms · Signal word Danger · Hazard statements H225 Highly flammable liquid and vapour. H412 Harmful to aquatic life with long lasting effects. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. (Contd. on page 2) GB



Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.02.2023

Version number 1.3

Revision: 20.02.2023

GB

Trade name: IRSA DD- Wetterfest achatgrau ca. RAL 7038

	(Contd. of page 1)
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P35	3 <i>IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].</i>
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/ international regulations.

• Additional information:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

· 2.3 Other hazards

*

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

• Dangerous components:		
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide	<20%
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	>5-<15%
EINECS: 203-603-9	🚸 Flam. Liq. 3, H226	
CAS: 123-86-4	n-butyl acetate	>5-<10%
EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	
CAS: 1330-20-7	xylene	>5-<10%
EINECS: 215-535-7	♦ Flam. Liq. 3, H226; ♦ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	>5-<10%
EINECS: 265-199-0	♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ Acute Tox. 4, H332; STOT SE 3, H335	
CAS: 7727-43-7	barium sulphate, natural	<5%
EINECS: 231-784-4	substance with a Community workplace exposure limit	
CAS: 78-93-3	butanone	<5%
EINECS: 201-159-0	🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 100-41-4	ethylbenzene	1-<5%
EINECS: 202-849-4	 ♦ Flam. Liq. 2, H225; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ♦ Acute Tox. 4, H332 	
CAS: 149-57-5	2-ethylhexanoic acid	<0.25%
EINECS: 205-743-6	🚸 Repr. 2, H361d; 🚸 Acute Tox. 4, H312	



Page 3/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.02.2023

Version number 1.3

Revision: 20.02.2023

Trade name: IRSA DD- Wetterfest achatgrau ca. RAL 7038

• Additional information: For the wording of the listed hazard phrases refer to section 16.

(Contd. of page 2)

SECTION 4: First aid measures

- 4.1 Description of first aid measures
 - · General information:
 - Take affected persons out into the fresh air.
 - Immediately remove any clothing soiled by the product.
 - · After inhalation: Supply fresh air; consult doctor in case of complaints.
 - · After skin contact: Immediately wash with water and soap and rinse thoroughly.
 - · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
 - · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

 • 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
 • Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.

(Contd. on page 4)



Page 4/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.02.2023

Version number 1.3

Revision: 20.02.2023

(Contd. of page 3)

Trade name: IRSA DD- Wetterfest achatgrau ca. RAL 7038

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

• Storage:

• Requirements to be met by storerooms and receptacles: Store in a cool location.

- · Information about storage in one common storage facility: Not required.
- \cdot Further information about storage conditions:

Keep under lock and key and out of reach of children.

- Keep container tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

	Ingreatents with timit values that require monitoring at the workplace.	
	5-6 2-methoxy-1-methylethyl acetate	
	Short-term value: 548 mg/m³, 100 ppm	
	Long-term value: 274 mg/m³, 50 ppm	
S	Sk	
123-86	6-4 n-butyl acetate	
WEL S	Short-term value: 966 mg/m³, 200 ppm	
I	Long-term value: 724 mg/m ³ , 150 ppm	
1330-2	20-7 xylene	
WEL S	Short-term value: 441 mg/m ³ , 100 ppm	
L	Long-term value: 220 mg/m ³ , 50 ppm	
S	Sk; BMGV	
7727-4	43-7 barium sulphate, natural	
WEL I	Long-term value: 10* 4** mg/m ³	
	*inhalable dust **respirable dust	
78-93-	-3 butanone	
WEL S	Short-term value: 899 mg/m ³ , 300 ppm	
	Long-term value: 600 mg/m ³ , 200 ppm	
S	Sk, BMGV	
100-41	1-4 ethylbenzene	
WEL S	Short-term value: 552 mg/m³, 125 ppm	
I	Long-term value: 441 mg/m ³ , 100 ppm	
S	Sk	
	· Ingredients with biological limit values:	
1330-2	20-7 xylene	
BMGV	/ 650 mmol/mol creatinine	
	Medium: urine	
	Sampling time: post shift	
	Parameter: methyl hippuric acid	
	(Contd	. on page



Page 5/10

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.02.2023

Version number 1.3

Revision: 20.02.2023

Trade name: IRSA DD- Wetterfest achatgrau ca. RAL 7038

78-93-3	butanone	(Contd. of page 4
	70 μmol/L	
	Medium: urine	
	Sampling time: post shift	
	Parameter: butan-2-one	
I		The lists valid during the making were used as basis.
8 2 Frn	osure controls	
	Personal protective equipment:	
1	· General protective and hy	vojenic measures
		oiled and contaminated clothing
	Wash hands before break	
	· Respiratory protection:	
		or low pollution use respiratory filter device. In case of intensive or longe
		ed respiratory protective device.
	· Protection of hands:	
	Protective glow	ves
	The glove material has to	be impermeable and resistant to the product/ the substance/ the preparation
		recommendation to the glove material can be given for the product/ th
	preparation/ the chemical	
		aterial on consideration of the penetration times, rates of diffusion and th
	degradation	
	· Material of gloves	
	Nitrile rubber, NB	R
	marks of quality an of several substance	he suitable gloves does not only depend on the material, but also on furthe nd varies from manufacturer to manufacturer. As the product is a preparatio ces, the resistance of the glove material can not be calculated in advance an e checked prior to the application.
	· Penetration time of	
		brough time has to be found out by the manufacturer of the protective glove
	and has to be obse	
	· Eye protection:	
	Tightly sealed	goggles
SECTI	ON 9: Physical and chemica	al properties
9.1 Info	rmation on basic physical and	chemical properties
	General Information	energia proportion
	· Appearance:	
	· Form:	Fluid
	· Colour:	Grey
	· Odour:	Characteristic
		(Contd. on page 6
		(Conta. on page (



Page 6/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.02.2023

Version number 1.3

Revision: 20.02.2023

Trade name: IRSA DD- Wetterfest achatgrau ca. RAL 7038

	(Contd. of page
· Odour threshold:	Not determined.
· pH-value:	Not determined.
• Change in condition • Melting point/freezing point • Initial boiling point and boi	
· Flash point:	-9 °C
· Flammability (solid, gas):	Highly flammable.
· Decomposition temperature	: Not determined.
• Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
• Explosion limits: • Lower: • Upper:	1.5 Vol % 10.8 Vol %
· Vapour pressure at 20 °C:	5 hPa
• Density at 20 °C: • Relative density • Vapour density • Evaporation rate	~1.232 g/cm ³ Not determined. Not determined. Not determined.
• Solubility in / Miscibility with • water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/war	ter: Not determined.
• Viscosity: • Dynamic: • Kinematic at 20 °C:	Not determined. 50 s (DIN 53211/4)
• Solvent content: • Organic solvents: • VOC (EC)	39.4 % 39.40 %
· Solids content:	60.6 %
• 9.2 Other information No	o further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

• 10.2 Chemical stability • Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 7)

⁻ GB -



Page 7/10

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.02.2023

Version number 1.3

Revision: 20.02.2023

(Contd. of page 6)

Trade name: IRSA DD- Wetterfest achatgrau ca. RAL 7038

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available date	<i>a, the classification criteria are not met.</i>
--	--

· LD/LC50 values relevant for classification:

AIE (ACU	-	Estimates)
Dermal	LD50	26,461–33,077 mg/kg
Inhalative	LC50/4 h	>59.1–70.5 mg/l
13463-67-	7 titanium	dioxide
Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.82 mg/l (rat)
108-65-62	e-methoxy-	1-methylethyl acetate
Oral	LD50	8,532 mg/kg (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)
123-86-4 n	i-butyl ace	tate
Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)
1330-20-7	xylene	
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
64742-95-	6 Solvent n	haphtha (petroleum), light arom.
Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)
78-93-3 bu	itanone	
Oral	LD50	3,300 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rabbit)
100-41-4 е	thylbenzer	10
Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rabbit)
149-57-52	ethylhexa	nnoic acid
Oral	LD50	3,000 mg/kg (rat)
Dermal	LD50	1,260 mg/kg (rabbit)
		y irritant effect:
		Skin corrosion/irritation Based on available data, the classification criteria are not met. Serious eye damage/irritation Based on available data, the classification criteria are not me

(Contd. on page 8)



Page 8/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.02.2023

Version number 1.3

Revision: 20.02.2023

Trade name: IRSA DD- Wetterfest achatgrau ca. RAL 7038

• Additional toxicological information:

(Contd. of page 7)

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
 - · Ecotoxical effects:
 - **Remark:** Harmful to fish
 - · Additional ecological information:
 - · General notes:
 - Harmful to aquatic organisms
 - Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number		
· ADR/RID/ADN, IMDG, IATA	UN1263	
14.2 UN proper shipping name		
· ADR/RID/ADN	1263 PAINT	
·IMDG	PAINT	
·IATA	Paint	



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.02.2023

Page 9/10

Version number 1.3

Revision: 20.02.2023

Trade name: IRSA DD- Wetterfest achatgrau ca. RAL 7038

(Contd. of page 8) · 14.3 Transport hazard class(es) · ADR/RID/ADN, IMDG, IATA 3 Flammable liquids. · Class · Label 3 · 14.4 Packing group II · ADR/RID/ADN, IMDG, IATA · 14.5 Environmental hazards: Not applicable. Warning: Flammable liquids. · 14.6 Special precautions for user · Hazard identification number (Kemler code): 33 · EMS Number: F-E, S-E· Stowage Category В · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: · ADR/RID/ADN 5L· Limited quantities (LQ) Code: E2 · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · Transport category 2 • Tunnel restriction code D/E· IMDG \cdot Limited quantities (LQ) 5LCode: E2 \cdot Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml UN 1263 PAINT, 3, II · UN "Model Regulation":

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

 \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

 \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

(Contd. on page 10)



Version number 1.3

Page 10/10

Printing date 20.02.2023

Revision: 20.02.2023

(Contd. of page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Trade name: IRSA DD- Wetterfest achatgrau ca. RAL 7038

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

- · Department issuing SDS: Abteilung Umweltschutz
- · Contact: -
- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Carc. 2: Carcinogenicity – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

 \cdot * Data compared to the previous version altered.