

Article Print c Versic	late:	KG40905ADX10 17.02.2023 15.0001	IRSA Platinum Revision date: 11.0 Issue date: 18.11.2		55080 EN Page 1 / 8	
SEC	TION 1: Ide	entification of the	substance/mixtu	re and of the company	//undertaking	
1.1.	product ide	entifiers				
		manufacturer/supp /designation	ier)	KG40905ADX10 IRSA Platinum 2K Öl-Grundierung schwarz		
1.2.	Relevant ic	lentified uses of th	e substance or mix	ture and uses advised a	gainst	
	paint and/or	lentified uses: r paint related mate or industrial and pro				
		ed against: for injecting or spra	ying.			
1.3.	Details of t	he supplier of the	safety data sheet			
	IRSA LACK Irmgard Sal An der Gün	FABRIK linger GmbH	rter/downstream us	er/distributor) Telephone: 0049 8282 8 Telefax: 0049 8282 8944		
	Laboratory	t responsible for in petent person)	nformation:	0049 8282 89440 info@irsa.de		
1.4.	Emergency Giftnotruf Fi	<b>/ telephone numbe</b> reiburg	r	0049 761 19240		
SEC	SECTION 2: Hazards identification					
2.1.	Classificat	-	egulation (EC) No 1	<b>272/2008 [CLP]</b> g to regulation (EC) No 12 <sup>:</sup>	72/2008 [CLP].	
2.2.	Label elem	ents				
	Labelling according to Regulation (EC) No. 1272/2008 [CLP]					
	Hazard pic	tograms				
	Hazard sta	<b>tements</b> not appli	cable			
	Precaution	ary statements				
		not appli	cable			
	Hazard cor	nponents for label not appli				
	Supplemer EUH208	ntal hazard informa Contains		May produce an allergic re	eaction.	

EUH208Contains phthalic anhydride. May produEUH210Safety data sheet available on request.

2.3. Other hazards

Spontaneous ignition possible through autoxidation of cloths soaked in the product. (The same applies to dust and other paint-soaked items). The product itself is not self ignitive.

#### Other information

Read label before use. If medical advice is needed, have product container or label at hand. Keep out of reach of children.

### **SECTION 3: Composition/information on ingredients**

3.2. Mixtures

DescriptionOils/waxes, containing solvents, aromatics removedClassification according to Regulation (EC) No 1272/2008 [CLP]



cle No.: t date: sion:	KG40905ADX10 17.02.2023 15.0001	IRSA Platinum Revision date: 11.02.2023 Issue date: 18.11.2022	55080 EN Page 2 / 8	
EC No. CAS No. Index No.	REACH Designa classifi			weight-%
918-167-1	Hydroca	472146-39-XXXX arbons, C11-C12, isoalkanes, < 2% arc q. 3 H226 / Asp. Tox. 1 H304	omatics	7,5 - 10
252-104-2 34590-94-8	3 (2-meth	450011-60-XXXX oxymethylethoxy)propanol ice with a common (EC) occupational	exposure limit value.	5 - 7,5

Full text of classification: see section 16

# SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### **General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

#### In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

#### Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

#### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### **Following ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

#### Unsuitable extinguishing media

strong water jet

#### 5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

#### 5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

### 6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing



Article No.:	KG40905ADX10	IRSA Platinum
Print date:	17.02.2023	Revision date: 11.02.2023
Version:	15.0001	Issue date: 18.11.2022

55080 EN Page 3 / 8

agents. Do not use solvents.

### 6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

# SECTION 7: Handling and storage

# 7.1. Precautions for safe handling

# Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

#### **Further information**

Vapours are heavier than air. Vapours form explosive mixtures with air.

## 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

#### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

#### Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 25 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

#### 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### Occupational exposure limit values:

(2-methoxymethylethoxy)propanol EC No. 252-104-2 / CAS No. 34590-94-8

WEL, TWA: 308 mg/m3; 50 ppm Remark: (may be absorbed through the skin)

#### Additional information

TWA : Long-term occupational exposure limit value STEL : short-term occupational exposure limit value Ceiling : peak limitation

#### DNEL:

(2-methoxymethylethoxy)propanol

EC No. 252-104-2 / CAS No. 34590-94-8

DNEL long-term dermal (systemic), Workers: 283 mg/kg

DNEL long-term inhalative (systemic), Workers: 308 mg/m<sup>3</sup>

DNEL long-term dermal (systemic), Consumer: 121 mg/kg

DNEL long-term inhalative (systemic), Consumer: 37,2 mg/m<sup>3</sup>

DNEL long-term exposure oral (systemic effects), Consumer: 36 mg/kg

PNEC:

(2-methoxymethylethoxy)propanol EC No. 252-104-2 / CAS No. 34590-94-8



Article No.:	KG40905ADX10	IRSA Platinum
Print date:	17.02.2023	Revision date: 11.02.2023
Version:	15.0001	lssue date: 18.11.2022

55080 EN Page 4 / 8

PNEC aquatic, freshwater: 19 mg/L PNEC aquatic, marine water: 1,9 mg/L PNEC aquatic, intermittent release: 190 mg/L PNEC sediment, freshwater: 70,2 mg/kg PNEC sediment, marine water: 7,02 mg/kg PNEC, soil: 2,74 mg/kg PNEC sewage treatment plant (STP): 4168 mg/L

#### 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

#### Personal protection equipment

#### **Respiratory protection**

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

#### Hand protection

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber) Thickness of the glove material > 0.4 mm : Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove

manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

#### Eye/face protection

Wear closely fitting protective glasses in case of splashes.

#### **Body protection**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

#### **Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

#### Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	black
Odour:	characteristic
Odour threshold:	not applicable
Melting point/freezing point:	not applicable
Initial boiling point and boiling range:	179 °C
	Source: Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics
Flammability:	Combustible liquid.
Lower and upper explosion limit:	
Lower explosion limit:	1,1 Vol-%
Upper explosion limit:	14 Vol-%
<b>_</b> , , , , ,	Source: (2-methoxymethylethoxy)propanol
Flash point:	> 61 °C
Auto-ignition temperature:	207 °C
	Source: (2-methoxymethylethoxy)propanol
Decomposition temperature:	not applicable
pH at 20 °C:	not applicable
Cinematic viscosity (40°C):	< 135 mm²/s



Article Print o Versio	date:	KG40905ADX10 17.02.2023 15.0001	IRSA Platinum Revision date: 1 Issue date: 18.1		55080 EN Page 5 / 8
	Viscosity	at 20 °C:		28 s 4 mm Method: DI	N 52211
	Solubility	(ies):		Method. Di	11 33211
		lubility at 20 °C:		insoluble	
	Partition	coefficient: n-octane	ol/water:	see section	n 12
	Vapour p	ressure at 20 °C:		<b>0,7 mbar</b> Method: ca Source: Hy	llculated. /drocarbons, C11-C12, isoalkanes, < 2% aromatics
	Density a Density a	nd/or relative densit at 20 °C:	ty:	<b>0,94 g/cm³</b> Method: IS	O 2811, part 3
	Relative v	/apour density:		not applica	able
	particle c	haracteristics:		not applica	able
9.2.	Other info				
	Solvent s	eparation test:		< 3 weight-	% (ADR/RID)
SEC	TION 10:	Stability and react	ivity		
10.1.	Reactivity	<b>y</b> ation available.			
10.2.	Chemical Stable wh section 7.	en applying the recor	mmended regulati	ons for stora	age and handling. Further information on correct storage: refer to
10.3.		t <b>y of hazardous reac</b> by from strong acids, s		strong oxidiz	ing agents to avoid exothermic reactions.
10.4.	<ul> <li>Conditions to avoid</li> <li>Hazardous decomposition byproducts may form with</li> </ul>			with exposur	e to high temperatures.
10.5.	<b>Incompat</b> not applic	t <b>ible materials</b> able			
10.6.	Hazardou	Is decomposition pr s decomposition bype trogen oxides.		with exposu	re to high temperatures, e.g.: carbon dioxide, carbon monoxide
SEC	TION 11:	Toxicological info	rmation		
11.1.	Informati	on on hazard classe	es as defined in F	Regulation (I	EC) No 1272/2008
	Acute tox	licity			
	oral, LD	xymethylethoxy)propa 50, Rat: > 5000 mg/kg LD50, Rabbit: > 5000	9		
	Skin corr	osion/irritation; Seri	ious eye damage	/eye irritatio	n
	(2-methox Skin no irritati eyes	xymethylethoxy)propa ion	nol		
		ory or skin sensitisa	tion		
	(2-methox	(ymethylethoxy)propa	nol		
	•	cts (carcinogenicity		nd toxicity fo	or reproduction)
		available data, the cl		-	
		gle exposure; STOT			
	(2-methox	kymethylethoxy)propa ation No data available	nol		
	Aspiratio	n hazard			
	(a) (i				

(2-methoxymethylethoxy)propanol



Article No.:	KG40905ADX10	IRSA Platinum	
Print date:	17.02.2023	Revision date: 11.02.2023	55080 EN
Version:	15.0001	Issue date: 18.11.2022	Page 6 / 8

Aspiration hazard; Evaluation Represents no obvious danger of aspiration due to its physical properties Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics

Aspiration hazard

#### Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

#### **Overall assessment on CMR properties**

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

## 11.2. Information on other hazards

#### Endocrine disrupting properties

No information available.

#### **SECTION 12: Ecological information**

Classification according to Regulation (EC) No 1272/2008 [CLP] There is no information available on the preparation itself. Do not allow to enter into surface water or drains.

#### 12.1. Toxicity

(2-methoxymethylethoxy)propanol Fish toxicity, LC50, Pimephales promelas (fathead minnow): 10000 mg/L (96 h) Daphnia toxicity, EC50, Daphnia magna (Big water flea): 1919 mg/L (48 h)

# 12.2. Persistence and degradability

(2-methoxymethylethoxy)propanol : 75 % (28 D); Evaluation Readily biodegradable (according to OECD criteria). Method: OECD F :93 % (13 D) Method: OECD 302B/ ISO 9888/ EEC 92/69/V, C.9

#### 12.3. Bioaccumulative potential

(2-methoxymethylethoxy)propanol Partition coefficient: n-octanol/water: 1,01

#### 12.4. Mobility in soil

(2-methoxymethylethoxy)propanol

: Evaluation No data available

## 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Endocrine disrupting properties No information available.

# 12.7. Other adverse effects

No information available.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

#### Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

# List of proposed waste codes/waste designations in accordance with EWC

080112 waste paint and varnish other than those mentioned in 08 01 11

#### Appropriate disposal / Package Recommendation



55080 EN Page 7 / 8

Article No.:	KG40905ADX10	IRSA Platinum
Print date:	17.02.2023	Revision date: 11.02.2023
Version:	15.0001	Issue date: 18.11.2022

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

		recycled. Vessels not properly emptied are special waste.				
SEC.	TION 14: Transport information					
	No dangerous good in sense of this	s transport regulation.				
14.1.	UN number or ID number	not applicable				
11 2	UN proper shipping name	not applicable				
14.2.	on proper simpling name					
14.3.	Transport hazard class(es)					
		not applicable				
14.4.	Packing group					
445	Environmental haranda	not applicable				
14.5.	Environmental hazards	not opplicable				
	Land transport (ADR/RID)	not applicable				
14 6	Marine pollutant	not applicable				
14.0.	Special precautions for user	d asfa containers. Make ours that nersons transporting the product know what to do it				
	case of an accident or leakage. Advices on safe handling: see parts 6	d safe containers. Make sure that persons transporting the product know what to do in - 8				
	Further information					
	Land transport (ADR/RID)					
	Tunnel restriction code	-				
	Sea transport (IMDG)					
	EmS-No.	not applicable				
14.7.	Maritime transport in bulk according	g to IMO instruments				
	No transport as bulk according IBC - C	Code.				
SEC	TION 15: Regulatory information					
15.1.	Safety, health and environmental re	gulations/legislation specific for the substance or mixture				
	EU legislation					
	Directive 2012/18/EU on the control This product is not classified according	of major-accident hazards involving dangerous substances [Seveso-III-Directive g to Directive 2012/18/EU.				
	Directive 2010/75/EU on industrial e VOC-value (in g/L) ISO 11890-2: 137 VOC-value (in g/L) ASTM D2369: 137	emissions [Industrial Emissions Directive]				
	<b>Directive 2004/42/EC on the limitation of emissions of volatile organic compounds</b> VOC product category: (Cat. A/f) ; VOC limit value: 700 g/l Maximum VOC content of the product in a ready to use condition (in g/L): 137					
	National regulations					
	<b>Restrictions of occupation</b> Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).					
	Other information:					
	Switzerland: Volatile organic compounds (VOC) content in percent by weight: 15					
	Denmark: PR-No.: 4419950					
	MAL code (MAL code in mixture): 1-1					
15.2.	Chemical Safety Assessment	ixture a chemical safety assessment has been carried out:				

# **SECTION 16: Other information**

Full text of classification in section 3



Article No.: Print date: Version:	KG40905ADX10 17.02.2023 15.0001	IRSA Platinum Revision date: 11.02.2023 Issue date: 18.11.2022	55080 EN Page 8 / 8	
Flam. Liq. Asp. Tox. 1		Flammable liquids Aspiration hazard	Flammable liquid and vapour. May be fatal if swallowed and enters airways.	
Abbreviat	ons and acronyms	6		
ADREuropeaOELOccupatBLVBiologicaCASChemicaCLPClassificCMRCarcinogDINGermanDNELDerivedEAKVEuropeaECEffectiveECEuropeaENEuropea		an Agreement concerning the International Carriage of Dangerous Goods by Road tional Exposure Limit Value al Limit Value al Abstracts Service cation, Labelling and Packaging genic, Mutagenic and Reprotoxic Institute for Standardization / German industrial standard No-Effect Level an Waste Catalogue Directive e Concentration an Community an Standard		
IBC CodeInternational CoICAO-TIInternational CiGoods by AirIMDG CodeInternational MaISOInternational OrLCLethal ConcentrLDLethal DoseMARPOLMaritime PollutionOECDOrganisation forPBTpersistent, bioactPNECPredicted No EffREACHRegulations corUNUnited NationsVOCVolatile Organical		ional Civil Aviation Organization T	Equipment of Ships carrying Dangerous Chemicals in Bulk echnical Instructions for the Safe Transport of Dangerous	
		Dose e Pollution: The International Conve ation for Economic Cooperation an int, bioaccumulative, toxic ed No Effect Concentration ation, Evaluation, Authorisation and ions concerning the International C	ion ention for the Prevention of Pollution from Ships d Development	

#### **Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.