

Article No Print date Version:	e: 17.02.2		IRSA Platinum Revision date: 08.1 Issue date: 05.11.20		55080 EN Page 1 / 9	
SECTIO	ON 1: Identifica	tion of the	substance/mixtu	re and of the compa	any/undertaking	
A	roduct identifier rticle No. (manufa rade name/design		ier)	KW04000AHJ10 IRSA Platinum 2K Öl-Härter		
				UFI: QKX2-KA6F-H00	DD-08VK	
			e substance or mix	ture and uses advised	d against	
R	elevant identified eserved for indust	rial and pro	fessional use.			
	ses advised agai o not use for injec		ying.			
			safety data sheet			
	<mark>upplier (manufac</mark> RSA LACKFABRIK		ter/downstream use	er/distributor)		
lrı Aı	mgard Sallinger G n der Günz 15 -86489 Deisenhau	mbH		Telephone: 0049 8282 Telefax: 0049 8282 89		
D	epartment respo	nsible for i	nformation:			
	aboratory	,		0049 8282 89440		
1.4. E	-mail (competent p mergency teleph	-	r	info@irsa.de		
	iftnotruf Freiburg			0049 761 19240		
SECTIO	SECTION 2: Hazards identification					
2.1. C	1. Classification of the substance or mixture					
		-	egulation (EC) No 1			
			-	regulation (EC) No 127		
S	cute Tox. 4 / H332 kin Sens. 1 / H317 TOT SE 3 / H335		Acute toxicity (inhala Respiratory or skin s STOT-single exposu	ensitisation	Harmful if inhaled. May cause an allergic skin reaction. May cause respiratory irritation.	
2.2. L a	abel elements					
Li	abelling accordir	g to Regul	ation (EC) No. 1272/	2008 [CLP]		
н	azard pictograms	6				
<	U War	ning				
H H H	Hazard statementsH332Harmful if inhaled.H317May cause an allergic skin reaction.H335May cause respiratory irritation.					
P	recautionary stat 280 403 + P233	Wear pro	otective gloves and e a well-ventilated place	ye/face protection. e. Keep container tight	ly closed.	
н	azard componen	hexamet	hylene-di-isocyanate	oligomers (isocyanura	ite type)	
	upplemental haz UH204	ard informa	ation	oduce an allergic react		
R	estrictions on use	ording to I	REACH annex XVII, I	-		
2.3. O	ther hazards					
Ν	o information avai	lable.				
-						

Other information: If medical advice is needed, have product container or label at hand. Keep out of reach of



Article No.:	KW04000AHJ10	IRSA Platinum	
Print date:	17.02.2023	Revision date: 08.11.2022	55080 EN
Version:	10.0000	Issue date: 05.11.2022	Page 2 / 9

children. Read label before use.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

	ccording to Regulation (EC) No 1272/2008 [CLP]	
EC No. CAS No. Index No.	REACH No. Designation classification: // Remark	weight-%
931-274-8	01-2119485796-17-XXXX Hexamethylene diisocyanate, oligomers (isocyanurate type) Acute Tox. 4 H332 / Skin Sens. 1 H317 / STOT SE 3 H335 Acute toxicity estimate (ATE): ATE (inhalation, vapour): 0,40 mg/L	50 - 100
212-485-8 822-06-0 615-011-00-1	01-2119457571-37-XXXX hexamethylene-di-isocyanate Acute Tox. 3 H331 / Eye Irrit. 2 H319 / STOT SE 3 H335 / Skin Irrit. 2 H315 / Resp. Sens. 1 H334 / Skin Sens. 1 H317 Specific concentration limit (SCL): Resp. Sens. 1 H334 >= 0,5 / Skin Sens. 1 H317 >= 0,5	0,25 - 0,5

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

- 4.2. Most important symptoms and effects, both acute and delayed In all cases of doubt, or when symptoms persist, seek medical advice.
- 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.



Article No.:	KW04000AHJ10	IRSA Platinum
Print date:	17.02.2023	Revision date: 08.11.2022
Version:	10.0000	Issue date: 05.11.2022

55080 EN Page 3 / 9

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Use appropriate container to avoid environmental contamination. Fouled surfaces must be immediately cleaned with suitable solvents, Useable as such (flammable): water 45 vol.% ethanol or i-propanol 50 vol. % ammonia solution (density= 0.88) 5 vol.%

Alternative (non-flammable): sodium carbonate 5 vol.% water 95 vol.%.

Take up spilled residuals with the same agent and leave them for a few days in unclosed containers until there is no further reaction. Then, close the containers and dispose of them in accordance with the regulations for waste removal (refer to section 13).

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

People who spray this preparation should have regular pulmonary function tests.

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Be careful when opening used containers (excess pressure). Precautionary measures should be taken in order to reduce strain from humidity or water: CO2 is formed which may produce excess pressure in closed containers . Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers. Keep away from amines, alcohols and water.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 25 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

People who spray this preparation should have regular pulmonary function tests.



Article No.:	KW04000AHJ10	IRSA Platinum
Print date:	17.02.2023	Revision date: 08.11.2022
Version:	10.0000	Issue date: 05.11.2022

55080 EN Page 4 / 9

8.1. Control parameters

Occupational exposure limit values:

not applicable

DNEL:

hexamethylene-di-isocyanate

Index No. 615-011-00-1 / EC No. 212-485-8 / CAS No. 822-06-0 DNEL acute inhalative (local), Workers: 0,07 mg/m³ DNEL acute inhalative (systemic), Workers: 0,07 mg/m³ DNEL long-term inhalative (local), Workers: 0,035 mg/m³ DNEL long-term inhalative (systemic), Workers: 0,035 mg/m³

PNEC:

hexamethylene-di-isocyanate Index No. 615-011-00-1 / EC No. 212-485-8 / CAS No. 822-06-0 PNEC aquatic, freshwater: > 77,4 µg/L Scenedesmus subspicatus PNEC aquatic, marine water: > 7,74 µg/L Scenedesmus subspicatus PNEC aquatic, intermittent release: 774 µg/L PNEC sediment, freshwater: > 0,0133 mg/kg PNEC, soil: > 0,0026 mg/kg

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. When spraying, wear self-contained breathing apparatus. For other tasks a suitable respiratory system must be used, if local and room suction is not sufficient for keeping aerosol and solvent vapour concentration below the exposure limit values. (refer to Personal protection equipment.)

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour:	Liquid yellow
Odour:	characteristic
Odour threshold:	not applicable
Melting point/freezing point:	not applicable
Initial boiling point and boiling range:	not applicable
Flammability	Combustible liquid.



Article Print d Versio	late:	KW04000AHJ10 17.02.2023 10.0000	IRSA Platinum Revision date: 0 Issue date: 05.1		55080 EN Page 5 / 9
	Lower ex	l upper explosion li plosion limit: plosion limit:	mit	not applicable not applicable	
	Flash poin	it:		> 100 °C	
	Auto-igniti	ion temperature:		not applicable	
	Decomposition temperature:			not applicable	
	pH at 20 °C	C:		not applicable	
	Cinematic	viscosity (40°C):		< 700 mm²/s	
	Viscosity a	at 20 °C:		100 s 4 mm Method: DIN 53211	
	Solubility(Water sol	ies): ubility at 20 °C:		insoluble	
	Partition c	oefficient: n-octan	ol/water:	see section 12	
	Vapour pro	essure at 20 °C:		not applicable	
	Density and/or relative density: Density at 20 °C:		ty:	1,15 g/cm³ Method: ISO 2811, part 3	
	Relative vapour density:			not applicable	
	particle characteristics:			not applicable	
9.2.	Other info	rmation			
	Solid content:			99,60 weight-%	
	solvent co Organic s Water:			0 weight-% 0 weight-%	
	Solvent se	paration test:		< 3 weight-% (ADR/RID)	
SEC	TION 10: S	tability and react	ivity		
10.1.	Reactivity Reacts with		oon dioxide, produ	cing bursting hazard in close	d containers due to build-up of pressure.
10.2	2° Chamical stability				

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.Reacts with water, forming carbon dioxide, producing bursting hazard in closed containers due to build-up of pressure.

10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. **Incompatible materials** not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

hexamethylene-di-isocyanate oral, LD50, Rat: 746 mg/kg Method: OECD 401



Print date: 17.02.2023 Re	SA Platinum evision date: 08.11.2022 sue date: 05.11.2022
---------------------------	---

55080 EN Page 6 / 9

dermal, LD50, Rat: > 7000 mg/kg inhalative (dust and mist), LC50, Rat (4 h)

Hexamethylene diisocyanate, oligomers (isocyanurate type) oral, LD50, Rat: > 2500 mg/kg dermal, LD50, Rat: > 2000 mg/kg

inhalative (dust and mist), LC50, Rat: 0,402 mg/L (4 h)

Skin corrosion/irritation; Serious eye damage/eye irritation

hexamethylene-di-isocyanate Skin

eyes

Respiratory or skin sensitisation

May cause an allergic skin reaction.

hexamethylene-di-isocyanate

Skin:

Respiratory system:

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

May cause respiratory irritation.

hexamethylene-di-isocyanate

Specific target organ toxicity (single exposure), Irritation

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage. Because of the isocyanate components' properties of this and with consideration of similar preparations the following applies: This mixture may cause acute irritation and/or sensitization of airways which lead to tightness in thorax, short-breath and asthmatic complaints. After sensitization even concentrations below the exposure limit values may cause asthma. Repeated inhaling can lead to permanent illness of the respiratory tract.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP] Do not allow to enter into surface water or drains.

12.1. Toxicity

hexamethylene-di-isocyanate Daphnia toxicity, EC0, Daphnia magna (Big water flea): > 89 mg/L (48 h) Method: European Union Bacteria toxicity, EC50: 842 mg/L (3 h) Algae, Desmodesmus subspicatus: > 77,4 (72 h) Fish toxicity, LC0:, Danio rerio (zebrafish): > 82,7 mg/L Algae, NOEC, Desmodesmus subspicatus: 11,7 mg/L (72 h)

Long-term Ecotoxicity

Toxicological data are not available.

12.2. Persistence and degradability



Article No.:	KW04000AHJ10	IRSA Platinum	
Print date:	17.02.2023	Revision date: 08.11.2022	55080 EN
Version:	10.0000	lssue date: 05.11.2022	Page 7 / 9

hexamethylene-di-isocyanate

Biodegradation, 67/548/EWG, Anhang V, C.4.D.: 42 % (28 d); Evaluation Not readily biodegradable (according to OECD criteria)

12.3. Bioaccumulative potential

Toxicological data are not available.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. Handle contaminated packages in the same way as the substance itself. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080111* Waste paint and varnish containing organic solvents or other dangerous substances *Hazardous waste according to Directive 2008/98/EC (waste framework directive).

not applicable

not applicable

not applicable

Appropriate disposal / Package

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

No dangerous good in sense of this transport regulation.

14.1. UN number or ID number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

Land transport (ADR/RID)	not applicable
Marine pollutant	not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

Tunnel restriction code

Sea transport (IMDG) EmS-No.

not applicable



Article No.:	KW04000AHJ10	IRSA Platinum	
Print date:	17.02.2023	Revision date: 08.11.2022	55080 EN
Version:	10.0000	Issue date: 05.11.2022	Page 8 / 9

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive] This product is not classified according to Directive 2012/18/EU.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive] VOC-value (in g/L): 5

Use restriction according to REACH annex XVII, no.:

Restrictions on use

As from 24 August 2023 adequate training is required before industrial or professional use.

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Other information:

Switzerland:

Volatile organic compounds (VOC) content in percent by weight: 0

Denmark:

PR-No.: 2310126

MAL code (MAL code in mixture): 2,3

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Full text of classification in section 3:

	in section 5.	
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
STOT SE 3 / H335	STOT-single exposure	May cause respiratory irritation.
Acute Tox. 3 / H331	Acute toxicity (inhalative)	Toxic if inhaled.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Skin Irrit. 2 / H315	Skin corrosion/irritation	Causes skin irritation.
Resp. Sens. 1 / H334	Respiratory or skin sensitisation	May cause allergy or asthma symptoms or
		breathing difficulties if inhaled.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]				
Acute Tox. 4	Acute toxicity (inhalative)	Calculation method.		
Skin Sens. 1	Respiratory or skin sensitisation	Calculation method.		
STOT SE 3	STOT-single exposure	Calculation method.		

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous



Article No.: Print date: Version:	KW04000AHJ10 17.02.2023 10.0000	IRSA Platinum Revision date: 08.11.2022 Issue date: 05.11.2022	55080 EN Page 9 / 9
IMDG Code ISO LC LD MARPOL OECD PBT PNEC REACH RID UN VOC vPvB	Internation Lethal C Lethal D Maritime Organisa persister Predicter Registra Regulation United N Volatile O	onal Maritime Code for Dangerous onal Organization for Standardization oncentration e Pollution: The International Conver- ation for Economic Cooperation and nt, bioaccumulative, toxic d No Effect Concentration tion, Evaluation, Authorisation and ons concerning the International Ca	on ntion for the Prevention of Pollution from Ships I Development
	•••	•	

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.