



Lackfabrik Irmgard Sallinger GmbH

Technical data sheet

02/2023

IRSA Parkettfugendichtmasse

Sealing compound for parquet flooring joints and connection joints

Silicone-free, colourless and coloured

Basis: polymerised ester, silicone-free.

Areas of application: sealing of joints in parquet flooring and connection joints like e.g. sealed, oiled and untreated parquet flooring and untreated wood in interior fittings and wooden window manufacture.

Colours available: Maple (ash, pine), light oak, natural oak, beech red brown, white, grey, cherry, mahogany, bog oak, black, dark walnut, light maple.

Properties: solvent free – odourless – fast drying – good for sanding when fully cured – energy elastic – excellent self adhesiveness – UV resistant and rot proof – stretchable up to 15% - and can be further treated with all standard sealants, oils and waxes – temperature and water resistance of -20°C up to $+110^{\circ}\text{C}$ when fully cured.

Wider joints from approx. 5 mm should be underlaid with a round cord.

Method of Application:

The surface must be clean, dry, dust and grease free. If necessary degrease e.g. with IRSA Grundreinger G88 (Basic Cleaner). Cut the tip off the cartridge above the thread, screw-on the nozzle, cut it across diagonally and squeeze out using a hand gun or compressed air gun. If necessary, smooth out the compound immediately with a damp sponge. For gluing apply it in a wavy line. Avoid three-sided adhesions at all costs.

Drying:

Depending on the climate and volume it can be sealed over, oiled over and/or washed over after approx 4 to 6 hours. After 18 to 24 hours it can be sanded. After approx 2 to 3 days it can be subjected to full load and wear and tear (based on the grounds of ideal conditions of $+20^{\circ}\text{C}$ und 55% humidity). High humidity and damp under flooring delay the drying process considerably.

Temperature: Room/under flooring/ IRSA Parkettfugendichtmasse must be between $+6^{\circ}\text{C}$ and $+30^{\circ}\text{C}$ during application.

Storability:

Store and transport in cool (frost free) conditions. Storable for 1 year in an unopened, original cartridge. Close opened containers tightly and use up soon.

Please pay attention to the instructions on the label IRSA Parkettfugendichtmasse.

Protect from frost!

The advice given by us in word, writing and endeavour for the technical application is supplied to our best knowledge, but may, however, only be regarded as an indication without any obligation and does not exempt you from examining the supplied products yourself, if they are suitable for the procedure and purposes intended. Application, use and processing of the products are not within our range of control and supervision, but are at your responsibility exclusively. It goes without saying that we guarantee products of high and good quality, according to the samples. With publishing of new information the earlier technical data sheets loose validity.