



Lackfabrik Irmgard Sallinger GmbH

Technical Data Sheet

03/2023

## IRSA Pflegeöl

(maintenance oil – colourless and coloured)

### Fields of application:

For the care of oiled wood, bamboo, cotto and cork surfaces indoors that are subject to normal to heavy wear and have not been waxed. IRSA Pflegeöl can be used on surfaces treated with oils for maintenance and cleaning at the same time (carry out a test application).

### Work instructions/necessary preparations:

Remove sand or similar (abrasive effect) with a Hoover, broom or mop. Clean particularly dirty surfaces with IRSA Seifenreiniger (soap cleaner) or with IRSA Grundreiniger G 88 (basic cleaner) and then allow to dry for at least 24 hours.

### This is the best way to maintain the surface (frequency depending on appearance):

#### Manual care:

First remove very heavy soiling dry or with IRSA Seifenreiniger. Apply the well shaken IRSA Pflegeöl in fine doses to the pre-impregnated IRSA Öltuch (oil cloth) and wipe the dry surface. The IRSA Pflegeöl can also be applied directly to the dry surface in fine doses and evenly as required (heavier soiling, matt, slightly grey appearance). After 10 minutes, rub in any excess IRSA Pflegeöl dry with IRSA Blitzboy and beige pad.

#### Mechanical maintenance with a single-disc machine

First remove very heavy soiling dry or with IRSA Seifenreiniger. Apply the well shaken IRSA Pflegeöl finely dosed and evenly on the dry surface. Then rub the IRSA Pflegeöl in dry with the single-disc machine and beige pad. Use a green pad for particularly heavy soiling. Remove the dirt with an absorbent lint-free fleece cloth or IRSA Öltuch (oil cloth) (e.g. placed under the green pad/single-disc machine) immediately after dissolving.

#### Please note:

If dull, worn spots or punctual stains appear, simply treat only these spots with the IRSA Öltuch / beige pad and IRSA Pflegeöl. No damp oil film or oil splashes should remain on the surface! A film formation by the IRSA Pflegeöl is not desired. Ensure good ventilation. Do not walk on the floor until the IRSA Pflegeöl has dried completely to avoid footprints. Oxygen and temperature from +18° C accelerate the drying process. The drying time of pure IRSA Pflegeöl applied directly to the surface is at least 6 hours (at +20°C and 55% relative humidity). After drying, re-polish the surface (white pad).

#### Subsequent oiling:

During the cleaning process with IRSA Seifenreiniger, not only dirt but also the IRSA oil is removed from the surface over time. Therefore, the surface should be re-oiled as needed, e.g. when the wood appears grey or too dull and has become too susceptible to dirt. For re-oiling, the IRSA oil that was already used for the initial treatment should be used. Please refer to the relevant technical data sheet and the container labels of the respective IRSA oil.

### To maintain the value of the surface in the long term, follow the IRSA care instructions for oiled and waxed surfaces!

#### Consumption values for a care oil treatment (empirical values):

Depending on the application method, approx. 10 - 25 ml/m<sup>2</sup>, i.e. 0.45 litre of IRSA Pflegeöl is sufficient for ca. 50 m<sup>2</sup> of oiled surface.

#### Shelf life:

Can be stored for approx. 1 year if the container is well closed.

Note: WGK 1, Giscodex Ö60.

For further information, please refer to the container label and the Safety Data Sheet.

Our technical application advice, both verbal and written, and based on tests, is given to the best of our knowledge, but is to be regarded only as non-binding advice and does not release you from your own examination of the products supplied by us for their suitability for intended processes and purposes. Application, use and processing of the products are beyond our control and are therefore exclusively your responsibility. It goes without saying that we guarantee the consistent quality of our products in conformity with the sample. When a new "Technical Data Sheet" is published, the previous one loses its validity.