



Lackfabrik Irmgard Sallinger GmbH

Technical Data Sheet

10/2021

IRSA Pflegeöl Natur-Effekt (IRSA Care Oil Nature Effect)

Special care product for the care and maintenance of IRSA Natur-Effekt-Öl (IRSA Nature Effect Oil).

Care must always be carried out after the oil has been applied (see Technical Data Sheet of IRSA Natur-Effekt-Öl under Drying/Care).

Basis:

Refined emulsified natural oils, such as soybean and sunflower oil, water, lead- and cobalt-free drying agents, pot preservative (1,2-benzisothiazol-3(2H)-one (BIT) / zinc pyrithione.

Delivery form:

IRSA Pflegeöl Natur-Effekt is supplied as ready-to-use product.

Areas of use:

Is suitable for the care of wood which has been treated with IRSA Natur-Effekt-Öl.

Characteristics:

IRSA Pflegeöl Natur-Effekt forms a thin care product film on the surfaces treated with IRSA Natur-Effekt-Öl and freshens them up while the natural bright appearance is kept.

Working instructions:

Apply IRSA Pflegeöl Natur-Effekt to the IRSA Oil Cloth or directly to the surfaces to be treated and then spread evenly over the surface with the IRSA Blitzboy. Make sure that no IRSA Pflegeöl Natur-Effekt remains on the surface - it must be worked in completely.

Consumption:

Approx. 25-30 ml/m², i.e. 1 litre IRSA Pflegeöl Natur-Effekt is enough for approx. 30-40 m².

Drying/Final hardness:

Can be walked on after approx. 4 hours and can be fully stressed after it has been dried overnight. The drying times given refer to normal conditions (+20° C and 55 % rel. humidity). High humidity and low temperature delay drying. Good ventilation must be ensured.

Application temperature:

The substrate and IRSA Pflegeöl Natur-Effekt should not be processed below +15°C and not above +30°C.

Working tools:

IRSA offers particularly suitable tools for IRSA Pflegeöl Natur-Effekt: IRSA Blitzboy and IRSA Oil Cloth. Note: A perfect result can only be achieved with suitable tools.

Shelf life:

The product last for approx. 1 year in unopened original containers when stored in a cool, frost-free and dry place. Seal the opened containers tightly and use up soon as possible.

The Material Safety Data Sheet is available on request.

Our technical application advice, both verbal and written, is given to the best of our knowledge and on the basis of tests, but is regarded only as non-binding advice and does not release you from the obligation to test the products supplied by us for their suitability for the intended processes and purposes. The application, use and processing of the products beyond our control are therefore exclusively your responsibility. It goes without saying that we guarantee pattern-conforming and consistent quality of our products.. When a new "Product Information" is published, the previous one loses its validity.