



Lackfabrik Irmgard Sallinger GmbH

Technical Data Sheet

10/2017

IRSA Pflegeöl "neutral" (IRSA Care Oil "neutral") for brightly pigmented surfaces

For brightly coloured oil surfaces which should stay longer bright

Areas of use:

For maintenance of normal to strongly stressed brightly oiled wood, bamboo, cork surfaces indoors which were not waxed. The IRSA Pflegeöl "neutral" can be used on surfaces treated with bright oils for the care and for the maintenance at the same time (please carry out trial application).

Instruction and Preparation:

Remove sand or similar residues (sanding effect) with vacuum cleaner, broom or mop. Clean very dirty surfaces with IRSA Seifenreiniger (IRSA Soap Cleaner) or IRSA Grundreiniger G88 (IRSA Base Cleaner G88) first and proceed after approx. 24 hours drying time at the earliest.

Optimal Maintenance of the Surface (frequency depends on appearance)

Manual maintenance:

First remove very strong dirt in dry condition or with IRSA Seifenreiniger (IRSA Soap Cleaner). If required, the IRSA Pflegeöl "neutral" can be directly administered in exact doses onto the dry surface (stronger dirt, changed appearance) and equally applied. Depending on demand (e.g. high solid dirt, mat or slightly grey appearance), apply IRSA Care Oil directly on the dry surface thin end evenly. After 10 minutes work-in time use the IRSA Blitzboy-wiper and beige pad for dry rub-in of eventually surplus rests of IRSA Pflegeöl "neutral".

Maintenance by machine (one-disc-sanding machine):

First remove high solid dirt as mentioned above. Shake IRSA Pflegeöl "neutral" well before use, apply fine dosed and evenly onto the dry surface. Following rub-in thoroughly by machine with a beige pad.

Cautions:

With arising of mat, worn-off parts or punctual spots on the surface, re-treat with the IRSA Oil-tissue/beige pad and IRSA Pflegeöl "neutral". Avoid wet oil-films or splashes on the surfaces to prevent. A film-forming by IRSA Pflegeöl "neutral" is not required. Care for good air condition. Do not walk on the treated surface as long as pure applied IRSA Care Oil -tracks are visible. Air conditions and temperature from +18°C speed up the drying process. The drying time of the pure and directly applied IRSA Pflegeöl "neutral" is at least 6 hours (at +20°C and 55% rel. humidity). Re-polish the surface during the drying process with a white pad

For long-lasting value of the floor, follow the maintenance-instructions of the IRSA oiled and waxed surfaces.

Total Consumption-experiences for one Care-Oil- treatment

Depending on way of application approx. 10-25ml/m², i.e. 0,5l of IRSA Pflegeöl "neutral" lasts for approx. 20m² oiled surface.

Storage:

Shelf life in unopened original container for at least 10 months.

Indication:

Giscode Ö60

Further information available on the Safety Data Sheets and labels.

The advice given by us in word, writing and endeavour for the technical application is supplied to our best knowledge, but may, however, only be regarded as an indication without any obligation and does not exempt you from examining the supplied products yourself, if they are suitable for the procedure and purposes intended. Application, use and processing of the products are not within our range of control and supervision, but are at your responsibility exclusively. It goes without saying that we guarantee products of high and good quality, according to the samples. With the publishing of new information the earlier technical data sheets lose validity.